



## iPt Titrode

6.0471.300

Combined platinum ring electrode with a pH glass membrane as reference electrode and integrated memory chip for storing sensor data.

This maintenance-free electrode is suitable for redox titrations when the pH value remains constant, e.g.:

- Iodometry
- Chromatometry
- Cerimetry
- Permanganometry

This electrode is stored in distilled water.

iTrodes can be used on Titrando, Ti-Touch oder 913/914 meters.

Below, the accessories are grouped into Scope of delivery and Optional accessories.  
Please keep this printout at hand for ordering replacement material.  
These lists may be subject to change.

## Scope of delivery 6.0471.300

| Order Number                                                                        | Description                                                                                                                               | Quantity |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|----------|
| 6.1236.050                                                                          | <b>Sleeve with SGJ 14/12 mm</b><br><br>Sleeve with SGJ 14/12 mm, polyethylene.                                                            | 1 Stk    |
|    |                                                                                                                                           |          |
| 6.2008.040                                                                          | <b>Storage vessel</b><br><br>Together with 6.2008.050 storage vessel holder. it provides a support for the electrode on 807 Dosing Units. | 1 Stk    |
|  |                                                                                                                                           |          |

## Optional accessories

2.854.0010

**854 iConnect**



The 854 iConnect – Electrode cable and measuring amplifier for intelligent "iTrodes" electrodes (cable length 150 cm).