



LL ISE reference electrode

6.0750.100

Silver / silver chloride reference electrode with double junction system.

This reference electrode is well suited for:

- automated applications
- ion measurements
- surfactant titrations

The ground-joint diaphragm, which is insensitive to contamination, offers a constant and reproducible electrolyte outflow. Additionally, the reference electrolyte is gelified for even better signal stability. The sensor is delivered with $c(\text{KCl}) = 3 \text{ mol/L}$ as bridge electrolyte, which can be freely selected and exchanged as needed.

Below, the accessories are grouped into Scope of delivery and Optional accessories.
Please keep this printout at hand for ordering replacement material.
These lists may be subject to change.

Scope of delivery 6.0750.100

Order Number	Description	Quantity
6.1236.050	Sleeve with SGJ 14/12 mm Sleeve with SGJ 14/12 mm, polyethylene.	1 Stk
		
6.2008.040	Storage vessel Together with 6.2008.050 storage vessel holder. it provides a support for the electrode on 807 Dosing Units.	1 Stk
		

Optional accessories

6.2106.020

Strand / 1 m / 2 x B

Electrode cable with 2 x plug B (4 mm) for connecting electrodes with plug-in head B



6.2103.140

**Adapter black 2 mm plug / B
socket 4 mm**

For connecting plug B (4 mm) to 2 mm socket.



6.2308.020

**Electrolyte 3 mol/L KCl (250
mL)**

Electrolyte solution $c(\text{KCl}) = 3 \text{ mol/L}$, (for Ag/AgCl reference systems)



6.2310.010

Electrolyte KNO₃-1 mol/L 250 mL

Electrolyte solution KNO₃ 1 M (reference electrolyte for combined silver electrodes)



6.2320.000

TEABr 0.4 mol/L in ethylene glycol (250 mL)

Electrolyte solution TEABr (tetraethylammonium bromide in ethylene glycol), c(TEABr) = 0.4 mol/L



6.2106.060

Strand / 2 m / 2 x B

Electrode cable with 2 x plug B (4 mm) for connecting electrodes with plug-in head B

