



NIRS DS2500 Petro Analyzer

2.929.2000

Robust near-infrared spectroscopy for quality control of fuels, not only in laboratories but also in direct production environments.

The NIRS DS2500 Petro Analyzer is the tried and tested, flexible solution for quality control and routine analysis of fuels and is compliant with the standard ASTM D6122. Resistant to dust, moisture, and vibrations, the NIRS DS2500 Petro Analyzer is not only suitable for laboratory use, but also use in direct production environments.

The NIRS DS2500 Petro Analyzer covers the full spectral range from 400 to 2,500 nm and delivers accurate results in less than one minute. The NIRS DS2500 Petro Analyzer is ready for immediate use through pre-calibrations for gasoline, diesel, and kerosine and, thanks to its simple operation, supports users in their day-to-day routine tasks. In cases of larger-sized sample quantities, productivity can be considerably increased by using a flow-through cell in combination with a Metrohm sample robot.

Phạm vi giao hàng 2.929.2000

Qt.	Order no.	Description
-----	-----------	-------------

Robust near-infrared spectroscopy for quality control, not only in laboratories but also in production environments.

The DS2500 Liquid Analyzer is the tried and tested, flexible solution for routine analysis of liquids along the entire production chain. Its robust design makes the DS2500 Liquid Analyzer resistant to dust, moisture and vibrations, which means that it is eminently suited for use in harsh production environments.



The DS2500 Liquid Analyzer covers the full spectral range from 400 to 2500 nm, heats samples up to 80°C and is compatible with various disposable vials and quartz cuvettes. The DS2500 Liquid Analyzer is thus adaptable to your individual sample requirements and helps you obtain accurate and reproducible results in less than one minute. The integrated sample holder detection and the self-explanatory Vision Air Software also ensure simple and safe operation by the user.

In the case of larger-sized sample quantities, productivity can be considerably increased by using a flow-through cell in combination with a Metrohm sample robot.

Intelligent holder for disposable glass vials with 8 mm diameter



100 disposable glass vials (borosilicate) with an optical path length of 8 mm for analyses of liquids in transmission. The disposable vials are supplied with the associated stoppers (number of pieces = 100).

Compatible with:

- Holder OMNIS NIR, vial, 8 mm (6.07401.070)
- DS2500 holder for 8 mm disposable vials (6.7492.020)




1 PCS

6.6072.151

Voucher for petroleum pre-calibration

Voucher for one pre-calibration. Entitles you to order pre-calibration of one fuel (diesel, gasoline, kerosine)



1 PCS

6.7494.500

DS2500 Liquid Analyzer Heat Protection

DS2500 Liquid Analyzer Heat Protection as optional protection for analysis at high temperatures.



Vision Air - Universal spectroscopy software.

Vision Air Complete is a modern and simple-to-operate software solution for use in a regulated environment.



Overview of the advantages of Vision Air:

- Individual software applications with adapted user interfaces ensure intuitive and simple operation
- Simple creation and maintenance of operating procedures
- SQL database for secure and simple data management

The Vision Air Complete version (66072208) includes all applications for quality assurance using Vis-NIR spectroscopy:

- Application for instrument and data management
- Application for method development
- Application for routine analysis

Additional Vision Air Complete solutions:

- 66072207 (Vision Air Network Complete)
- 66072209 (Vision Air Pharma Complete)
- 66072210 (Vision Air Pharma Network Complete)

Phụ kiện tùy chọn

Order no.	Description	
6.7430.050	Spare lamp for NIRS DS2500	
	Spare lamp with 12.0 V and 35 W for NIRS DS2500 Analyzer	
6.7494.000	DS2500 Liquid Wavelength Calibration Standard	
	Intelligent transmission wavelength calibration standard for the DS2500 Liquid Analyzer	

Metrohm AG
Ionenstrasse 9100
Herisau info@metrohm.com