



Conductivity measuring cell $c = 0.5 \text{ cm}^{-1}$ with Pt1000 (fixed cable, 0.65 m)

6.00923.080

4-conductor conductivity measuring cell with cell constant $c = 0.5 \text{ cm}^{-1}$ (guide value), with integrated Pt1000 temperature sensor and with fixed cable (0.65 m) for connecting to the OMNIS Measuring Module Conductivity.

Thanks to the robust/break-proof plastic shaft made of PEEK, this sensor is mechanically very resistant and is suitable for measurements of medium conductivities, e.g., in:

- Drinking water
- Surface water
- Waste water

Phạm vi giao hàng 6.00923.080

Order Number	Description	Quantity
6.1236.050	Sleeve with SGJ 14/12 mm Sleeve with SGJ 14/12 mm, polyethylene.	1 Stk



Phụ kiện tùy chọn

6.2301.060

KCl ion standard 250 mL



KCl ion standard ($c(\text{ion}) = 0.1000 \pm 0.0005 \text{ mol/L}$), can also be used as standard solution for conductometry 12.87 mS/cm (25°C).

6.2324.010

**Conductivity standard $100 \mu\text{S}$
/cm 250 mL**



Conductivity standard for calibration of conductivity measuring cells with cell constant = $0.1/\text{cm}$.

6.2324.110

**Conductivity standard $100 \mu\text{S}$
/cm, 5 x 30 mL**



Conductivity standard for calibration of conductivity measuring cells with cell constant = $0.1/\text{cm}$.

6.02101.020

**Measuring module
conductivity**

Measurement channel for one OMNIS Titrator or Titration Module
for the connection of conductivity measuring cells.

