



Separate polymer membrane electrode, Ca

6.0508.110

Calcium-selective electrode with polymer membrane.

This ISE has to be used in combination with a reference electrode and is suitable for:

- ion measurements of Ca^{2+} in aqueous solutions
- ion measurements in small sample volumes (minimum immersion depth 1 mm)
- complexometric (back) titrations (e.g., determination of water hardness)

Thanks to a robust/break-proof plastic shaft made of PVC, this sensor is mechanically very resistant.

Phạm vi giao hàng 6.0508.110

Order Number	Description	Quantity
6.1236.050	Sleeve with SGJ 14/12 mm	1 Stk



Sleeve with SGJ 14/12 mm, polyethylene.

6.2008.040

Storage vessel

1 Stk



Together with 6.2008.050 storage vessel holder. it provides a support for the electrode on 807 Dosing Units.

Phụ kiện tùy chọn

6.2104.020

Electrode cable / 1 m / F



For connecting electrodes with Metrohm plug-in head G to Metrohm instruments (socket F).

6.0750.100

LL ISE reference electrode



Silver / silver chloride reference electrode with double junction system.

This reference electrode is well suited for:

- automated applications
- ion measurements
- surfactant titrations

The ground-joint diaphragm, which is insensitive to contamination, offers a constant and reproducible electrolyte outflow. Additionally, the reference electrolyte is gelified for even better signal stability. The sensor is delivered with $c(\text{KCl}) = 3 \text{ mol/L}$ as bridge electrolyte, which can be freely selected and exchanged as needed.