



5-ring conductivity measuring cell $c = 1.0 \text{ cm}^{-1}$ with Pt1000 (fixed cable 2 m)

6.0920.130

5-ring conductivity measuring cell with cell constant $c = 1.0 \text{ cm}^{-1}$ (guide value), with integrated Pt1000 temperature sensor and fixed cable (2.0 m) for connecting to an 856 Conductivity Module in combination with a sample changer.

This sensor is suitable for automated measurements of medium conductivities, e.g., in:

- drinking water
- surface water
- wastewater

Phạm vi giao hàng 6.0920.130

Order Number	Description	Quantity
6.1236.050	Sleeve with SGJ 14/12 mm Sleeve with SGJ 14/12 mm, polyethylene.	1 Stk



Phụ kiện tùy chọn

6.2324.110

Conductivity standard 100 μ S/cm, 5 x 30 mL



Conductivity standard for calibration of conductivity measuring cells with cell constant = 0.1/cm.

6.2324.010

Conductivity standard 100 μ S/cm 250 mL



Conductivity standard for calibration of conductivity measuring cells with cell constant = 0.1/cm.

6.2301.060

KCl ion standard 250 mL



KCl ion standard ($c(\text{ion}) = 0.1000 \pm 0.0005 \text{ mol/L}$), can also be used as standard solution for conductometry 12.87 mS/cm (25 °C).