



Driving axle for rotating disk electrode (RDE) with mercury contact

6.1204.220

Driving axle for rotating disk electrode (RDE) with titanium axle and mercury contact for VA measuring stands, M3 thread.

Phụ kiện tùy chọn

6.1204.130

Silver Electrode Tip



Metal electrode tip, silver (Ag). Electrode disk diameter 2 mm. M3 thread. Temperature range: 0 ... 40 °C.

6.1204.140

Gold Electrode Tip



Metal electrode tip, gold (Au). Electrode disk diameter 2 mm. M3 thread. Temperature range: 0 ... 40 °C.

6.1204.150

Lateral Gold Electrode Tip



Metal electrode tip, gold (Au), with lateral electrode surface. Electrode disk diameter 3 mm. M3 thread. Temperature range: 0 ... 40 °C.

6.1204.170

**3 mm platinum electrode tip
for CVS**

Metal electrode tip made of platinum (Pt), diameter of electrode disk 3 mm, polished surface, M3 thread connection. Temperature range: 0 - 40 °C.



6.1204.180

Ultra Trace electrode tip

Carbon electrode tip from Ultra Trace graphite. Electrode disk diameter 2 mm. M3 thread connection. Temperature range: 0 - 40 °C.



6.1204.190

**1 mm platinum electrode tip
for CVS**

Metal electrode tip made of platinum (Pt), diameter of electrode disk 1 mm ± 0.02 mm, polished surface, shaft made of glass, M3 thread connection. Concentricity error: 0.2 mm. Temperature range: 0 - 50 °C.



6.1204.610

**2 mm platinum electrode tip
for CVS**



Metal electrode tip made of platinum (Pt), diameter of electrode disk 2 mm $\pm$ 0.05 mm, polished surface, shaft made of glass, M3 thread connection. Concentricity error: 0.3 mm. Temperature range: 0 - 50 °C.

6.1204.600

**Glassy carbon electrode tip,
shaft made of glass.**



Carbon electrode tip made of Glassy-Carbon (GC). Diameter of electrode disk 2 mm $\pm$ 0.1 mm, polished surface, shaft made of glass, M3 thread connection, concentricity deviation: 0.25 mm. Temperature range: 0 - 50°C.