



Raman probe 638

DRP-RAMANPROBE638


Reflection probe designed to be used with a single excitation 638 nm wavelength (up to 300 mW). Suitable to work with DropSens Raman cell for screen-printed electrodes (ref. RAMANCELL), Raman cell for conventional electrodes (ref. RAMANCELL-C) or with any conventional Raman set-up.

Phụ kiện tùy chọn

DRP-RAMANCELL-C

**Raman
spectroelectrochemical cell
for conventional electrodes**

Cell in PEEK for Raman spectroelectrochemical measurements. Designed be used with ref. RAMANPROBE and conventional Metrohm electrodes.



DRP-SPELECRAMAN638

**Spectroelectrochemical
Raman instrument (638 nm
laser)**

SPELECRAMAN638 is an instrument for performing spectroelectrochemical Raman measurements. It combines in only one box a laser class 3B (638 nm $\pm$ 0.5), a bipotentiostat /galvanostat and a spectrometer (wavelength range 640 – 885 nm and Raman shift 50 – 4370 cm⁻¹) and includes a dedicated spectroelectrochemical software that allows optical and electrochemical experiments synchronization.



DRP-RAMANCELL

**Raman Cell for Screen-Printed
Electrodes**

Black teflon reflection cell for performing Raman Spectroelectrochemistry with screen-printed electrodes in combination with ref. RAMANPROBE.

