




"ProfIC 9 – Cation" – Professional IC System for trace analysis with Inline Calibration, Sample Preconcentration and Matrix Elimination

ProfIC-09-Cation

The Professional IC system with conductivity detection enables ultratrace analysis of cations or anions (non-suppressed) in the lowest ppt range (ng/L) in complex matrices. The "ProfIC 9" with Metrohm Inline Sample Preconcentration, Inline Calibration and Inline Matrix Elimination enables chromatography without limitation by the matrix and guarantees a long lifetime for the analytic separation column.

Schematic diagram

Phạm vi giao hàng ProfIC-09-Cation

Qt.	Order no.	Description
-----	-----------	-------------

1 PCS

ProfIC-Vario-09-Cation

"ProfIC Vario 9 Cation" – Professional IC Vario system with Metrohm's intelligent preconcentration technique and Inline Matrix Elimination (MiPCT-ME)

The Professional IC Vario system with Metrohm's intelligent inline preconcentration technique, Inline Matrix Elimination and conductivity detection enables ultratrace analysis down to the lowest ppt range (ng/L) of cations in complex matrices.

Typical areas of application:

- Ultratrace analysis in samples from nuclear power plants and conventional power plants
- Trace and ultratrace analysis in extraction agents and organics
- Trace analysis in snow and ice

Schematic representation

Installation instructions



1 PCS

2.800.0010

800 Dosino

The 800 Dosino is a drive with write/read hardware for intelligent Dosing Units. With fixed cable (length 150 cm).



1 PCS

2.850.9010

IC Conductivity Detector

Compact and intelligent high performance conductivity detector for intelligent IC instruments. Outstanding temperature stability, the complete signal processing within the protected detector block and the latest generation of DSP – Digital Signal Processing – guarantee the highest precision of the measurement. No change of measuring ranges (not even automatic ones) is required, due to the dynamic working range.



The 858 Professional Sample Processor processes samples from 500 µL to 500 mL. The sample transfer takes place either by means of a peristaltic pump on the 850 Professional IC system or with an 800 Dosino.



The Metrosep I Trap 1 - 100/4.0 column is used to eliminate ionic, i.e. cationic and anionic, contaminants from aqueous solutions. Its use is especially recommended for the purification of the transfer water in combination with "MISP" or "Metrohm Inline Sample Preparation". Using the Metrosep I Trap 1 - 100/4.0 column can significantly reduce the influence of the transfer water on the system blank.



807 Dosing Unit with integrated data chip with 10 mL glass cylinder and light protection, mountable to a reagent bottle with ISO/DIN GL 45 glass thread. FEP tubing connection, antidiffusion tip.



Accessories set for mounting a Dosino on intelligent IC instruments for Liquid Handling.



Phụ kiện tùy chọn

Order no.	Description	
6.1010.310	Metrosep C PCC 1 HC/4.0 For cation preconcentration and matrix elimination	
6.1050.420	Metrosep C 4 - 150/4.0 The Metrosep C 4 - 150/4.0 is the universal standard column in cation analysis for accomplishing high separating efficiency in a short time. The Metrosep C 4 - 150/4.0 is the ideal separation column for the analysis of alkaline and earth alkaline metals in aqueous media.	
6.1050.500	Metrosep C 4 Guard/4.0 The Metrosep C 4 Guard/4.0 contains the C-4 column material and is used to protect all Metrosep cation columns that have a substrate based on silica gel. Particles and contamination are reliably retained, considerably prolonging the service life of the analytical separation column. The economical price is an additional plus. The Metrosep C 4 Guard/4.0 also works based on the "On Column Guard System" and is screwed directly onto the separation column with virtually no dead volume.	
6.1608.080	Bottle / 300 mL Rinsing vessel for IC Sample Processors.	

6.2041.390

Sample rack, 16 x 100 mL, (PVC)

Sample rack for 810 Sample Changer, 814 USB Sample Processor, 855 Robotic Titrosampler "Light", suitable for 16 sample beakers. The following sample beakers can be used: 100 mL beakers, short.

Plastic: Polyvinyl chloride (PVC)



6.2820.000

Al foil

1,000 rondels with a diameter of 80 mm. Foil thickness: 0.010 mm. Together with 6.2037.040 foil holder for 6.1432.210 sample beaker and 6.2037.080 foil holder for 6.1459.300 sample beaker.



6.5333.000

IQ/OQ Kit for IC

The IQ/OQ Kit contains all parts and standard solutions required for IQ /OQ in ion chromatography.



6.5620.000

Connection set to 807 Dosing Unit: Port 4

For the connection of an M6 tubing to Port 4 on an 807 Dosing Unit (transition from luer to M6), including holder safety device

