

"ProfIC Vario 5 AnCat" – Professional IC Vario system with Metrohm's intelligent preconcentration technique (MiPCT)

ProfIC-Vario-05-AnCat

The Professional IC Vario system with **Metrohm's intelligent inline sample preconcentration, sequential suppression** and **conductivity detection** enables fully automatic determination of anions and cations in solutions with low ion concentration.

Typical areas of application:

– Numerous applications, ranging from ultrapure water analysis to drinking water analysis
– Analyses of different samples from power plants
– Process control and monitoring of rinsing solutions, e.g., in the semiconductor industry
– Trace analysis in snow and ice

Schematic representation

Metrohm

Installation instructions

Phạm vi giao hàng ProfIC-Vario-05-AnCat

Order Number	Description	Quantity
2.940.2500 	**940 Professional IC Vario TWO/SeS/PP** The 940 Professional IC Vario TWO/SeS/PP is the intelligent two-channel IC instrument with sequential suppression (one channel) and a peristaltic pump for suppressor regeneration. The instrument can be used with any separation and detection methods. Typical areas of application: – Standard instrument for parallel anion and cation determinations – Trace analysis for anions and cations – Online monitoring for anions and cations	1 PCS
2.850.9010 	**IC Conductivity Detector** Compact and intelligent high performance conductivity detector for intelligent IC instruments. Outstanding temperature stability, the complete signal processing within the protected detector block and the latest generation of DSP – Digital Signal Processing – guarantee the highest precision of the measurement. No change of measuring ranges (not even automatic ones) is required, due to the dynamic working range.	2 PCS
2.800.0010 	**800 Dosino (cable: 1.5 m)** The 800 Dosino is a drive with write/read hardware for intelligent dosing units. With permanently attached cable (length 1.5 m).	2 PCS

6.5330.140

IC equipment: MiPCT 2 PCS



Accessory set for Inline Preconcentration (MiPCT) including Liquid Handling Station, left.

2.786.0040

786 Swing Head 2 PCS



Additional equipment for Robotic Sample Processors XL without titration or transfer heads.

6.1462.030

Robotic arm with transfer head for 786 Swing Head, left swinging 1 PCS



Transfer robotic arm for liquid handling purposes

6.1462.040

Robotic arm with transfer head for 786 Swing Head, right swinging 1 PCS

Transfer robotic arm for liquid handling purposes



6.2064.000

Beaker retainer for Advanced IC Sample Processor 1 PCS


Retaining plate for 838 Advanced Sample Processors. For holding 2.5 or 11 mL vials.



6.2064.010

Beaker retainer for Professional IC Sample Processor, right 1 PCS

Retaining plate for Professional IC Sample Processors. For holding 2.5 or 11 mL vials.



6.2833.000

Needle/tube holder 1/8 in.

2 PCS



For IC/VA Sample Processors. For 1/8 in. tubes

6.2629.000

Screw nut to needle holder IC

2 PCS




On Sample Processors

6.9927.028

Safety shield for IC, right and left

2 PCS



Safety shield for 815 Robotic USB Sample Processor XL (2T /0P). Is utilized in IC when sample needles are used.

6.2846.010

Sample needle made of zirconium oxide with PEEK tip

2 PCS



Sample needle for Sample Processors and Autosampler in ion chromatography. The PEEK tip guarantees secure piercing of the vial covering.

6.2841.130

Liquid Handling Station, right 1 PCS



Combined rinsing and dilution station for sample changers with two towers and a Swing Head. To be assembled to the right of the tower.

2.815.0130

815 Robotic USB Sample Processor XL (2T/0P) 1 PCS



Robotic USB Sample Processor XL for the automatic processing of routine samples in series with large quantities and for complex sample preparation or parallel runs. Up to four pumps (membrane or peristaltic) and three dosing devices for Liquid Handling tasks can be connected.

Because of the multitude of application variants, rack, stirrer, titration head, robotic arm, Swing Head, and sample vessels must be tailored to the application and ordered separately.
The control is "stand alone" using Touch Control. The following software products can be selected for the PC control: tiamo™ titration software, MagIC Net chromatography software, viva voltammetry software, or OMNIS.

Phụ kiện tùy chọn

6.9920.191
Sample rack, 35 x 60 mL and 3 x 250 mL (PVC)



Sample rack for 858 Professional Sample Processor, 815 Robotic USB Sample Processor XL, suitable for 35 sample vessels and 3 rinsing bottles. The following sample vessels and rinsing bottles can be used: 6.1608.100, 60 mL and 250 mL Nalgene FEP vessels. Plastic: Polyvinyl chloride (PVC)

6.1608.100
PE bottle 50 mL



Bottle for Extension Module Liquid Handling.

6.2820.000
Al foil



1,000 rondels with a diameter of 80 mm. Foil thickness: 0.010 mm. Together with 6.2037.040 foil holder for 6.1432.210 sample beaker and 6.2037.080 foil holder for 6.1459.300 sample beaker.

6.1050.420

Metrosep C 4 - 150/4.0



The Metrosep C 4 - 150/4.0 is the universal standard column in cation analysis for accomplishing high separating efficiency in a short time. The Metrosep C 4 - 150/4.0 is the ideal separation column for the analysis of alkaline and earth alkaline metals in aqueous media.

6.1050.500

Metrosep C 4 Guard/4.0



The Metrosep C 4 Guard/4.0 contains the C-4 column material and is used to protect all Metrosep cation columns that have a substrate based on silica gel. Particles and contamination are reliably retained, considerably prolonging the service life of the analytical separation column. The economical price is an additional plus. The Metrosep C 4 Guard/4.0 also works based on the "On Column Guard System" and is screwed directly onto the separation column with virtually no dead volume.

6.1010.310

Metrosep C PCC 1 HC/4.0



For cation preconcentration and matrix elimination

6.2842.000

MSM-HC Rotor A



Suppressor rotor for all IC instruments with MSM-HC (Metrohm Suppressor Module with high capacity)

6.2844.000
MSM-LC Rotor A

Suppressor rotor for use with 2 mm columns.



6.2832.000
MSM Rotor A

Suppressor rotor for all IC instruments with MSM (Metrohm Suppressor Module)



6.2842.020
Adapter sleeve, MSM

Not only the MSM Rotor A but also the MSM-LC Rotor A can be installed in the rotor housing with the aid of the adapter sleeve.



2.941.0010
941 Eluent Production Module

The 941 Eluent Production Module enables the automatic production of an eluent. It enables continuous working without manual intervention and guarantees stable retention times. It can be combined with all Metrohm IC instruments and is monitored by MagIC Net.



6.5330.090
IC equipment: Additional eluent on the Eluent Production Module

Accessory set for Eluent Production Module. Contains all parts necessary for expansion by one eluent. The level sensor must be ordered in accordance with the application.



2.800.0010
800 Dosino (cable: 1.5 m)

The 800 Dosino is a drive with write/read hardware for intelligent dosing units. With permanently attached cable (length 1.5 m).



6.2769.110
EMPTY sensor for level sensor for 2 L bottles

This sensor, mounted in the 6.1626.000 bottle attachment, results in the level sensor EMPTY for 2 L bottles. Included are two sensor rods, one aspiration tubing and two holders for fixing the tubing to one of the sensor rods.



6.6059.422

MagIC Net 4.2 Professional: 1 license

Professional chromatography software from Metrohm for controlling all intelligent Professional IC systems, Compact IC systems and their peripherals, all detectors and the various Auto samplers, 800 Dosino, 771 Compact Interface, etc. The software permits checks, data acquisition, data evaluation and data monitoring as well as report generation of ion chromatographic analyses.

Graphical user interface for routine operations, extensive database programs, method development, configuration and manual control panel; very flexible user management, efficient database operations, extensive data export functions, individually configurable report generator, control and monitoring of all system components and the chromatography results.

MagIC Net Professional complies fully with FDA Regulation 21 CFR Part 11 as well as GLP.

MagIC Net is available in 15 dialog languages: German, English, Chinese, Traditional Chinese, French, Italian, Spanish, Portuguese, Bulgarian, Czech, Hungarian, Japanese, Korean, Russian, Slovakian

With this version, the graphic user interface has been modernized, which improves, among other things, the scaling and sharpness of the user interface on 4K monitors.

1 license

The installation and documents are supplied on a USB flash drive.

6.6059.423

MagIC Net 4.2 Multi: 3 licenses

Client/server-compatible chromatography software from Metrohm for controlling all intelligent Professional IC systems, Compact IC systems and their peripherals, all detectors and the various Autosamplers, 800 Dosino, 771 Compact Interface, etc.
The software permits checks, data acquisition, data evaluation and data monitoring as well as report generation of ion chromatographic analyses.
Data and method are centrally stored on a Server.

Graphical user interface for routine operations, extensive database programs, method development, configuration and manual control panel; very flexible user management, efficient database operations, extensive data export functions, individually configurable report generator, control and monitoring of all system components and the chromatography results.
MagIC Net Multi complies fully with FDA Regulation 21 CFR Part 11 as well as with GLP.
MagIC Net is available in 15 dialog languages: German, English, Chinese, Traditional Chinese, French, Italian, Spanish, Portuguese, Bulgarian, Czech, Hungarian, Japanese, Korean, Russian, Slovakian
With this version, the graphic user interface has been modernized, which improves, among other things, the scaling and sharpness of the user interface on 4K monitors.
Performance for client/server systems with servers outside the in-house company network has been improved.
Client/server version with 3 licenses