



## Application Note AN-PAN-1035


# 在分析印染浴中的、保粉及其他参数

The size of the indigo molecule makes it difficult to dye synthetic fibers, but the large pores of cellulose (such as in cotton) accept it readily. Indigo is insoluble in water, so it must first be reduced to the water-soluble leuco-indigo form by sodium hydrosulfite in a strong alkaline bath. Good circulation within the bath is imperative for consistent dye coverage, but care must be taken not to introduce any oxygen. Fabrics must be oxidized between dips in the dye bath to set the indigo within the pores of the fibers, but multiple dips are necessary for darker, uniform


coverage.

This Process Application Note is focused on monitoring indigo, hydrosulfite, and other parameters in textile dye baths using the 2035 Potentiometric and 2060 TI Process Analyzers from Metrohm Process Analytics. Many critical parameters need to be monitored and controlled to ensure high quality of the end product: the pH value for proper NaOH (alkali) dosage, the concentrations of both hydrosulfite and indigo, as well as the temperature of the bath and even the redox potential.





Indigo




Leuco Indigo



www.metrohm.com

Multiple baths are necessary to properly dye fabrics along with circulation systems to keep concentrations stable throughout the vat because of the colloidal nature of the large dye molecule. Textiles are dipped in and gently moved around the circulating hot dye baths to ensure uniform coverage without introducing excess oxygen. Multiple dips are required for a darker blue color in the finished product, with care taken to oxidize the fabric between each dip in order to trap the leuco-indigo within the fibers. The oxidized indigo will not rinse out easily when the fabric is washed because it is now water-insoluble again. Synthetic fabrics are more difficult to dye with indigo because the large molecules have more difficulty penetrating their tightly packed fibers.

 **Metrolink**

need to be controlled for continuous dyeing processes: the pH for proper NaOH (alkali) dosage, the concentrations of both  $\text{Na}_2\text{S}_2\text{O}_4$  and indigo, as well as the temperature of the vat. The redox potential of the dye bath also needs to be controlled for proper dyeing of the fabric.

Manual laboratory methods can be quite cumbersome and can introduce bias depending on the analyst. Therefore, the complexity of the process necessitates inline or online analysis of the dye baths for the most precise results. A great choice for online monitoring the indigo,

hydrosulfite, and other parameters such as pH and conductivity in dye baths is the **2035 Process Analyzer - Potentiometric (Figure 1)** from Metrohm Process Analytics. Together with the plant circulation system, these fast-responding online process analyzers can help keep the dye bath throughput high without losing money from excess chemical consumption due to inefficient processes, ensuring the quality of the dyed fabric remains constant.

## INTRODUCTION



**Figure 1.** 2035 Potentiometric Analyzer from Metrohm Process Analytics.

## APPLICATION

The simultaneous monotonic titrations of hydrosulfite and indigo in indigo dye baths are performed in a closed vessel under nitrogen gas with potassium ferricyanide ( $\text{K}_4\text{Fe}[\text{CN}]_6$ ) as a titrant and a reagent mix (NaOH + dispersing

agent). The Metrohm Process Analytics 2035 Potentiometric and 2060 TI Process Analyzers (**Figures 1 and 2**) are ideally suited for the fully automatic execution of these analyses, as well as additional parameters like pH or conductivity.

**Table 1.** Textile dye bath measurement parameters

Parameters	Range
Hydrosulfite	0.25–4 g/L
Indigo	0.25–7 g/L (can be expanded to measure higher ranges)

## REMARKS

The analysis of sodium hydrosulfite and indigo must be carried under N<sub>2</sub> gas in order to prevent the evaporation and oxidation of dye with ambient air. If the sample line contains fabric

particles, it needs to be filtered before the sample inlet of the analyzer to prevent blockages. This method can also be used for loop dyeing applications for threads and yarns.

## CONCLUSION

The Metrohm Process Analytics 2060 TI Process Analyzer and 2035 Potentiometric Process Analyzer can not only measure the concentration of indigo and hydrosulfite, but

also pH and conductivity measurements to give an overall health status of the dye baths without delay.



**Figure 2.** 2060 TI Process Analyzer from Metrohm Process Analytics.

## BENEFITS FOR TITRATION IN PROCESS

- Detect process upsets via automated analysis.
- Increased product throughput, reproducibility, production rates, and profitability.
- Better color uniformity is achieved by constantly monitoring the chemical composition of the baths.
- Fully automated diagnostics – automatic alarms for when bath samples are out of the specified parameters.




## CONTACT

瑞士万通中国  
北京市海淀区上地路1号院  
1号楼7702  
100085 北京

marketing@metrohm.com.cn

## CONFIGURATION



### 2035 Process Analyzer Potentiometric

用于位滴定和子性量的 2035 Process Analyzer 程分析,可使用用和滴定行分析。此外,版本的 2035 Process Analyzer 程分析用于使用万通高性能行子性分析。一准的准溶液技是理品基的靠方法。

此位分析款型的分析可提供当前市上所有量技的准果。滴定法作常用的分析方法之一,具有超 1000 用可供使用,能分析数百成,从酸/元素直到解池中金属度,可用于几乎任何行。

滴定法是目前使用广泛的化学方法之一。技易行,无需校准。

可用于此配置的部分滴定:

- 位分析滴定
- 使用光技的比色滴定
- 基于·休滴定法定水



## 2060 Process Analyzer

2060 Process Analyzer 是在湿化学分析,用于无数用。此程分析提供了一个新的模化概念,由一个称«主机»的中心平台成。

主机由部分成。上部包含触摸屏和工算机。下部含有柔性取部,其中放有用于分析的硬件。如果主取部容量不足以分析挑,那主机可以展多四个外的取部机,以保有足的空来具挑性的用。附加机的配置方式使每个取部机可以与具有集成(非接触式)液位的合使用,以增加分析的正常行。

2060 Process Analyzer 提供不同的湿化学技:滴定法、舍滴定法、光度定、直接量和准添加入法。

足所有目要求(或足的所有需求),可提供品理系,以保分析解决方案可靠。我可以提供任何品理系,如冷却或加、和脱气、等。