

# Accessories for 2.940.2100

Below, the accessories are grouped into Scope of delivery and Optional accessories.  
Please keep this printout at hand for ordering replacement material.

These lists may be subject to change.

## Scope of delivery 2.940.2100

Qty.	Order no.	Description	
1 pcs	1.940.2100	<b>940 Professional IC Vario TWO</b>	
The 940 Professional IC Vario TWO is the intelligent <b>two-channel</b> IC instrument <b>without suppression</b> . The instrument can be used with any separation and detection methods.			
Typical areas of application:			
<ul style="list-style-type: none"><li>Two-channel applications without suppression for the determination of anions, cations, carbohydrates or polar, organic compounds</li><li>Combinations with conductivity, UV/VIS or amperometric detection</li></ul>			
1 pcs	6.1825.220	<b>PEEK sample loop 100 µL</b>	 For injection valve, with 2 PEEK pressure screws
1 pcs	6.5000.000	<b>Accessory kit: Vario/Flex Basic</b>	 Basic set of accessories for a Professional IC Vario or Compact IC Flex.
2 pcs	6.5000.010	<b>Accessory kit: Vario/Flex ONE</b>	 Set of accessories for the ONE Module (IC pump with injector) for Professional IC Vario and Compact IC Flex instruments.

## Optional accessories

Order no.	Description	
<b>2.800.0010</b>	<b>800 Dosino</b>	Drive with write/read hardware for intelligent Dosing Units. With fixed cable (length 150 cm). 
<b>2.800.0020</b>	<b>800 Dosino</b>	Drive with write/read hardware for intelligent dosing units. With permanently attached cable (length 0.65 m). 
<b>2.815.4110</b>	<b>815 Robotic Soliprep for LC</b>	The 815 Robotic Soliprep for LC is a complete system for the <a href="#">completely automatic preparation of samples</a> which need to be dissolved, homogenized, diluted or filtered prior to their determination. The samples are conveyed directly into the injector of the chromatograph after preparation. 
<b>2.850.9010</b>	<b>IC Conductivity Detector</b>	Compact and intelligent high performance conductivity detector for intelligent IC instruments. Outstanding temperature stability, the complete signal processing within the protected detector block and the latest generation of DSP – Digital Signal Processing – guarantee the highest precision of the measurement. No change of measuring ranges (not even automatic ones) is required, due to the dynamic working range. 
<b>2.850.9110</b>	<b>IC Amperometric Detector</b>	Compact and intelligent amperometric detector for intelligent IC instruments. Outstanding selectivity due to the four measuring modes: DC, PAD, flexIPAD and CV, as well as the excellent signal/noise ratio and the very fast stabilization of the measuring signal guarantee the highest in measurement precision. 

---

**2.858.0010      858 Professional Sample Processor**

The 858 Professional Sample Processor processes samples from 500 µL to 500 mL. The sample transfer takes place either by means of a peristaltic pump on the 850 Professional IC system or with an 800 Dosino.



---

**2.858.0020      858 Professional Sample Processor – Pump**

The 858 Professional Sample Processor – Pump processes samples from 500 µL to 500 mL. The sample transfer takes place either with the installed bidirectional two-channel peristaltic pump or with an 800 Dosino.



---

**2.858.0030      858 Professional Sample Processor – Pump – Injector**

The 858 Professional Sample Processor – Pump – Injector processes samples from 500 µL to 500 mL. The sample transfer takes place either with the installed bidirectional two-channel peristaltic pump or by means of an 800 Dosino. In addition, a six-way injection valve is available for the sample preparation.



---

**2.863.0010      863 Compact IC Autosampler**

The 863 Compact IC Autosampler is the ideal help for routine analysis. It enables automation of the full range of Metrohm IC instruments.



---

**2.889.0010      889 IC Sample Center**

The 889 IC Sample Center is a robust Autosampler for high sample throughput, optimized for the challenges of the modern analytic laboratory. It works in accordance with the x-y-z principle and a syringe control with high resolution for precise sample injection. A double needle system enables the penetration of vessel caps and septa. A PEEK injection valve completes the automation system of the 889 IC Sample Center. It is the appropriate automation solution when you have only a very small amount of sample.



---

**2.889.0020      889 IC Sample Center – cool**

The 889 IC Sample Center – cool is the appropriate automation solution when you have only a very small amount of sample. In comparison with the 889 IC Sample Center, it possesses in addition a cooling function and is thus the ideal sample changer for biochemically relevant or thermally unstable samples.



---

**2.919.0020      919 IC Autosampler plus**

The 919 IC Autosampler plus fulfills the requirements of laboratories with medium sample numbers. It enables automation of the full range of Metrohm IC instruments.



---

**2.941.0010      941 Eluent Production Module**

The 941 Eluent Production Module enables the automatic production of an eluent. It enables continuous working without manual intervention and guarantees stable retention times. It can be combined with all Metrohm IC instruments and is monitored by MagIC Net.



---

**2.942.0020      942 Extension Module Vario Prep 2**

The 942 Extension Module Vario Prep 2 is an extension module for the Professional IC Vario line of instruments. It multiplies the possibilities of **Inline Sample Preparation** and **Liquid Handling** in Professional IC Vario systems.



Typical applications

- Inline Dialysis in two-channel Vario systems
- Inline Dialysis in systems without sample changers
- Column switching and cutting techniques

---

**2.942.0040      942 Extension Module Vario HPG**

The 942 Extension Module Vario HPG is an extension module for the Professional IC Vario line of instruments. It permits the addition of a further eluent in a Professional IC Vario **high-pressure gradient system**.



Typical applications

- High-pressure gradient systems with up to four eluents

---

**2.942.0070      942 Extension Module Vario LQH**

The 942 Extension Module Vario LQH is an extension module for the Professional IC Vario line of instruments. It expands the possibilities of **Metrohm Inline Sample Preparation "MISP"** and **Liquid Handling and opens a Professional IC system for Online Monitoring**.



Typical applications:

- **Extended Inline Sample Preparation**
- **Online monitoring**
- **Dilution without sample changers**
- **Fully automatic sample derivation reactions**

---

**2.942.0300      942 Extension Module Vario ChS/PP**

The 942 Extension Module Vario ChS/PP is an extension module for the Professional IC Vario line of instruments. It permits the integration of a complete **chemical suppression** with a **peristaltic pump** for suppressor regeneration or **Inline Neutralization** or **Inline Cation Removal**, respectively, in a Professional IC Vario system.



Typical applications:

- Chemical suppression for 2nd analysis channel
- Inline Neutralization/Cation Removal

---

**2.942.0500      942 Extension Module Vario SeS/PP**

The 942 Extension Module Vario SeS/PP is an extension module for the Professional IC Vario line of instruments. It permits the integration of a complete **sequential suppression** with a **peristaltic pump** for suppressor regeneration in a Professional IC Vario system.



Typical applications:

- Sequential suppression for an additional analysis channel

---

**2.942.1060      942 Extension Module Vario ONE/Deg**

The 942 Extension Module Vario ONE/Deg is an extension module for the Professional IC Vario line of instruments. It permits the installation of an additional **IC analysis channel** in a Professional IC Vario system.



Typical applications:

- Parallel anion and cation analysis with low-pressure gradient
- Parallel anion and cation analysis with Inline Neutralization
- Additional analysis channel with UV/VIS or amperometric detector

---

**2.943.0110      943 Professional Reactor Vario**

The 943 Professional Reactor Vario is a heatable reactor, especially developed for pre- and post-column derivatization. It captivates by its robustness, the fast heating rate and the possibility of carrying out reactions at up to 150 °C.



---

**2.943.0210      943 Professional Thermostat Vario**

The 943 Professional Thermostat Vario is a stand-alone column oven for up to two columns with a maximum length of 150 mm. It captivates by its fast heating rate and the possibility of operating two separation columns together at up to 80°C.



---

**2.944.0010      944 Professional UV/VIS Detector Vario**

The 944 Professional UV/VIS Detector Vario is the intelligent UV/VIS detector from Metrohm. It permits a secure and reliable quantification of substances active in the ultraviolet or visible range. Detection takes place via a Diode Array.



---

**2.945.0010      945 Professional Detector Vario – Conductivity**

Intelligent stand-alone detector equipped with a high-performance IC Conductivity Detector. For use with intelligent IC instruments or as independent conductivity detector.



---

**2.945.0020      945 Professional Detector Vario – Amperometry**

Intelligent stand-alone detector equipped with the IC Amperometric Detector. Outstanding selectivity due to the four measuring modes: DC, PAD, flexIPAD, CV. The excellent signal/noise ratio and the very fast start-up guarantee the highest in measurement precision. For use with intelligent IC instruments or as independent detector.



---

**2.945.0030      945 Professional Detector Vario – Conductivity & Amperometry**

Intelligent stand-alone detector equipped with the high performance IC Conductivity Detector and the IC Amperometric Detector, with the four measuring modes DC, PAD, flexIPAD and CV. For use with intelligent IC instruments or as independent detector for conductivity and amperometric detection.



---

**6.2617.040      Tool for piston seal, macro**

For removing and assembling the piston seal for all macro pump heads



---

**6.2741.000      Piston seal**

For all IC pumps. Particularly well-suited for eluents with organic solvents.



---

**6.2741.040 PE/PTFE piston seal, macro**

For all macro pump heads



---

**6.2824.130 Macro pump head PEEK**

Macro pump head for intelligent IC instruments, flow range 0.1...20 mL/min, maximum pressure 12.5 MPa.



---

**6.6059.322 MagIC Net 3.2 Professional CD: 1 license**

Professional PC program for controlling all of the intelligent Professional IC systems, Compact IC instruments and their peripherals, such as various Autosamplers, 800 Dosinos, 771 Compact Interface, etc. The software permits the inspection, data acquisition, data evaluation, data monitoring and report generation of ion chromatographic analyses.

Graphical user interface for routine operations, extensive database programs, method development, configuration and manual system control; very flexible user administration, efficient database operations, extensive data export functions, individually configurable report generator, control and monitoring of all system components and the chromatography results.

MagIC Net Professional complies fully with FDA Regulation 21 CFR Part 11 as well as GLP.

MagIC Net is available in 16 dialog languages.

1 license.

---

**6.6059.323 MagIC Net 3.2 Multi CD: 3 licenses**

Professional PC program for controlling all of the intelligent Professional IC systems, Compact IC instruments and their peripherals, such as various Autosamplers, 800 Dosinos, 771 Compact Interface, etc. The software permits the inspection, data acquisition, data evaluation, data monitoring and report generation of ion chromatographic analyses.

Graphical user interface for routine operations, extensive database programs, method development, configuration and manual system control; very flexible user administration, efficient database operations, extensive data export functions, individually configurable report generator, control and monitoring of all system components and the chromatography results.

MagIC Net Multi complies fully with FDA Regulation 21 CFR Part 11 as well as with GLP.

MagIC Net is available in 16 dialog languages.

Client/server version with 3 licenses.