




## Accessories for 2.865.0010

Below, the accessories are grouped into Scope of delivery and Optional accessories. Please keep this printout at hand for ordering replacement material. These lists may be subject to change.

### Scope of delivery 2.865.0010

Qty.	Order no.	Description
1 pcs	1.865.0010	<p><b>865 Dosimat plus</b></p> <p>Universal dispensing unit for titration and dosing tasks in the laboratory. Including push-button cable for manual dispensing control and 6.3026.220 exchange unit (20 mL). A multitude of instruments can be connected at the USB interface of the Dosimat plus, even a number of them simultaneously when a USB hub is used (keyboard, mouse, USB compact printer or USB DIN A4 printer, USB Memory Stick for methods and data backup). The optional 6.2148.030 USB/RS-232 Adapter Box enables the connection of laboratory balances and operation with a computer.</p> <p>With its four dosing modes, the Dosimat plus offers a multitude of applications:</p> <p>DOS (Dosing) – Dosing at the press of a button</p> <p>This mode is particularly suitable for performing manual titrations with indicator. A result can be calculated and a result report can be printed automatically from the dosed volume.</p> <p>XDOS (Extended dosing) – Controlled dosing</p> <ul style="list-style-type: none"> <li>• Fixed volume dosing: The volume and the dosing rate are specified.</li> <li>• Time-controlled dosing: The volume and the time are specified.</li> <li>• Dosing according to dosing rate: The dosing rate and the time are specified.</li> </ul> <p>If continuous dosing without interruption is required, then the 865 Dosimat plus can be operated together with an 805 Dosimat in tandem mode.</p> <p>CNT D (Content dosing) – Preparation of standard and other solutions.</p> <p>The volume of the solvent to be dosed is determined automatically on the basis of the sample size of the starting substance (solid or stock solution) and the specified target concentration.</p> <p>LQT (Liquid transfer) – Pipetting and diluting of liquids.</p>
		
1 pcs	6.2107.100	<p><b>Manual dosing controller</b></p> <p>Manual dosing controller for dosing and manual titration with the Dosimat plus</p>
		
1 pcs	6.2151.100	<p><b>Adapter USB MINI (OTG) - USB A</b></p> <p>For connecting USB instruments.</p>
		

---

**1 pcs**      **6.2739.010**      **Wrench**  
For exchange units.



---

**1 pcs**      **6.3026.220**      **Exchange Unit 20 mL**  
Exchange unit with integrated data chip with 20 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, anti-diffusion buret tip and standard amber glass reagent bottle.



## Optional accessories

Order no.	Description
-----------	-------------

**2.142.0100**      **Custom Q3X thermal printer**

Compact printer with USB interface for

- 900 Touch Control
- 915 KF Ti-Touch
- 916 Ti-Touch
- 917 Coulometer
- 877 / 848 Titrino plus
- 865 / 876 Dosimat plus
- 91X Meter (6.2151.140)
- Eco Dosimat / Titrator



Paper width 60 mm (40 characters). Including 6.2151.120 USB cable.

---

**2.801.0040**      **801 Stirrer with stand**

Magnetic stirrer including base plate, support rod and electrode holder for supplementing the Titrino plus, Dosimat plus, Titrandos, Sample Processors, 805 Dosimat and 780/781 pH meters as well as the 856 and 867 measuring modules. With permanently attached cable for MSB (Metrohm Serial Bus).



---

**2.802.0040**      **802 Stirrer (propeller stirrer) for 804 Ti Stand**

Rod stirrer with 6.1909.010 Propeller stirrer.



---

**2.804.0040 804 Ti Stand with stand**

Titration stand and controller for 802 Rod Stirrer. The 804 Ti Stand together with the optional 802 Rod Stirrer provides an alternative to the magnetic stirrer. Ti Stand with base plate, support rod and electrode holder.



---

**6.1562.060 Pipetting equipment for Manual Dosing Controller**

Pipetting equipment for Manual Dosing Controller for 865 and 876 Dosimats.



---

**6.1562.140 Pipetting tubing 10 mL for 6.1562.060**

---

**6.2134.120 Cable RS-232 to Mettler AX**

Connecting Metrohm RS-232 interface to Mettler AX



---

**6.2141.240 Remote cable Dosimat plus - Compact Sample Changer/Titrino plus**

Cable for the remote connection between Dosimat plus and Compact Sample Changer and/or Titrino plus using 6.2141.260 Cable.



---

**6.2141.250 Remote cable Compact Sample Changer - Titrino**

Cable for the remote connection between Compact Sample Changer and Titrinos with 25-pin remote socket.



---

**6.2141.260 Remote cable Compact Sample Changer - Dosimat plus and Titrino plus**

Cable for remote connection between Compact Sample Changer and Dosimat plus and further devices (e.g. Titrino plus or Pump Station).



---

**6.2148.030 RS-232/USB Box**

Extends the Titrino plus by two RS-232 interfaces, e.g., for the connection of balances, PC (tiBase software), LIMS. Requires 6.2151.030 cable.



---

**6.2723.310 Protective cover for Titrino plus**

Protective cover for display and keypad for all instruments of the Titrino plus family.



Suitable for: 848 Titrino plus, 862 Compact Titrosampler, 863 Compact Autosampler, 865 Dosimat plus, 869 Compact Sample Changer, 870 KF Titrino plus, 876 Dosimat plus, 877 Titrino plus, 899 Coulometer.

---

**6.3026.110 Exchange Unit 1 mL**

Exchange Unit with integrated data chip with 1 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, antidiffusion buret tip and standard amber glass reagent bottle.



---

**6.3026.150 Exchange Unit 5 mL**

Exchange Unit with integrated data chip with 5 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, anti-diffusion buret tip and standard amber glass reagent bottle.



---

**6.3026.210 Exchange Unit 10 mL**

Exchange unit with integrated data chip with 10 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, anti-diffusion buret tip and standard amber glass reagent bottle.



---

**6.3026.250 Exchange unit 50 mL**

Exchange unit with integrated data chip with 50 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, antiodiffusion tip and standard amber glass reagent bottle.

