

2.942.0500

2.942.0500

1 1.942.0500 942 Extension Module Vario SeS/PP

The 942 Extension Module Vario SeS/PP is an extension module for the Professional IC Vario line of instruments. It permits the integration of a complete **sequential suppression** with a **peristaltic pump** for suppressor regeneration in a Professional IC Vario system.

Typical applications:

- Sequential suppression for an additional analysis channel



1 6.1602.150 Bottle attachment / GL 45 - 3 x UNF 10/32

For the connection of 1/16 in. capillaries. Used in conjunction with MSM auxiliary solutions and in Metrohm Inline Sample Preparation.



1 6.1608.020 Glass bottle / 1000 mL / GL 45

Bottle for auxiliary solutions.



1 6.1803.030 PTFE capillary 0.5 mm i.d. / 3 m







Capillary for inline dialysis, for Dialysis Unit, IC Dialysis Sample Processor, IC Liquid Handling Dialysis Unit



2 6.1826.420 PharMed® pump tubing (orange/yellow), 3-stopper

For MSM regeneration with peristaltic pump.



1	6.1831.070 PEEK capillary 0.75 mm i.d., 70 cm For Advanced VA Sample Processor	
1	6.2156.070 Cable Extension Module - Professional IC, 1 m Cable connecting the extension module with the Professional IC instrument	
1	6.2251.000 Colored sleeves for capillaries Colored pieces of heat shrink tubing for capillary coding. Three pieces each of five different colors.	
1	6.2744.034 Coupling olive/UNF 10/32, 2x Connection between pressure screw and pump tubing. 2 pieces. For IC instruments with peristaltic pump.	
2	6.2744.180 Pump tubing connector with security lock and filter For the connection of a pump tubing and a capillary with built-in filter	
1	6.5000.020 Accessory kit: Vario/Flex SeS Set of accessories for sequential suppression (SeS) for Professional IC Vario and Compact IC Flex instruments. Without Suppressor Rotor.	

6.2103.170 Adapter to Leak Sensor at Professional IC

Adapter to connect two leak sensors to a Professional IC instrument



6.2832.000 MSM Rotor A

Suppressor rotor for all IC instruments with MSM (Metrohm Suppressor Module)



6.2842.000 MSM-HC Rotor A

Suppressor rotor for all IC instruments with MSM-HC (Metrohm Suppressor Module with high capacity)



6.2842.020 Adapter sleeve for Suppressor Vario

The use of the adapter sleeve makes it possible to install both the Standard MSM and the MSM-LC rotor in the MSM-HC housing.



6.2842.200 MSM-HC Rotor C

Suppressor rotor for all IC instruments with MSM-HC drive (Metrohm Suppressor Module with high capacity) for cation suppression.



6.2844.000

MSM-LC Rotor A

Suppressor rotor for use with 2 mm columns.

