

## 2.876.0010

### 2.876.0010

---

<b>1</b>	<b>1.876.0010</b>	<b>876 Dosimat plus</b>
----------	-------------------	-------------------------

Universal dispensing unit for manual titrations and dosings. Including push-button cable for manual dosing control and 20 mL exchange unit. A multitude of instruments can be connected at the USB interface of the Dosimat plus, even a number of them simultaneously when a USB hub is used (keyboard, mouse, USB compact printer or USB DIN A4 printer, USB Memory Stick for methods and data backup). The optional 6.2148.030 USB/RS-232 Adapter Box enables the connection of laboratory balances and operation with a computer. With its two dosing modes, the Dosimat plus offers the following applications:



DOS (Dosing) – Dosing at the press of a button

This mode is particularly suitable for performing manual titrations with indicator. A result can be calculated and a result report can be printed automatically from the dosed volume.

XDOS (Extended dosing) – Controlled dosing

- Fixed volume dosing: The volume and the dosing rate are specified.
- Time-controlled dosing: The volume and the time are specified.
- Dosing according to dosing rate: The dosing rate and the time are specified.

---

<b>1</b>	<b>6.2107.100</b>	<b>Manual dosing controller</b>
----------	-------------------	---------------------------------

Manual dosing controller for dosing and manual titration with the Dosimat plus



---

<b>1</b>	<b>6.2151.100</b>	<b>Adapter USB MINI (OTG) - USB A</b>
----------	-------------------	---------------------------------------

For connecting USB instruments.



- 
- 1**      **6.2739.010**      **Wrench**  
For exchange units.



- 
- 1**      **6.3026.220**      **Exchange Unit 20 mL**  
Exchange unit with integrated data chip with 20 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, anti-diffusion buret tip and standard amber glass reagent bottle.



---

**2.142.0100 Custom Q3X thermal printer**

Compact printer with USB interface for

- 900 Touch Control
- 915 KF Ti-Touch
- 916 Ti-Touch
- 917 Coulometer
- 877 / 848 Titrino plus
- 865 / 876 Dosimat plus
- 91X Meter (cable 6.2151.140)
- Eco Dosimat / Titrator
- 862 Compact Titrator
- 870 KF Titrino plus
- 899 Coulometer



Paper width 60 mm (40 characters). Including 6.2151.120 USB cable.

---

**2.801.0040 801 Stirrer with stand**

Magnetic stirrer including base plate, support rod and electrode holder for supplementing the Titrino plus, Dosimat plus, Titrandos, Sample Processors, 805 Dosimat and 780/781 pH meters as well as the 856 and 867 measuring modules. With permanently attached cable for MSB (Metrohm Serial Bus).



---

**2.805.0010 805 Dosimat**

Dosing device for the Titrandos and Sample Processors with read/write hardware for intelligent Exchange Units. With permanently attached cable. Without Exchange Unit.



---

**6.2134.120 Cable RS-232 to Mettler AX**

Connecting Metrohm RS-232 interface to Mettler AX



---

**6.2147.000 Numerical USB keypad**

Numerical USB keypad for Titrino plus, Dosimat plus, 862 Compact Titr sampler, 869 Compact Sample Changer, 863 Compact Autosampler and 899 Coulometer. With two integrated USB connectors.



---

**6.2148.030 RS-232/USB Box**

Extends the Titrino plus by two RS-232 interfaces, e.g., for the connection of balances, PC (tiBase software), LIMS. Requires 6.2151.030 cable.



---

**6.2151.120 Cable USB MINI (OTG) - USB B, 1.8 m**

For connecting USB instruments.



---

**6.2723.310 Protective cover for Titrino plus**

Protective cover for display and keypad for all instruments of the Titrino plus family.



Suitable for: 848 Titrino plus, 862 Compact Titr sampler, 863 Compact Autosampler, 865 Dosimat plus, 869 Compact Sample Changer, 870 KF Titrino plus, 876 Dosimat plus, 877 Titrino plus, 899 Coulometer.

---

**6.3026.110 Exchange Unit 1 mL**

Exchange Unit with integrated data chip with 1 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, antidiusion buret tip and standard amber glass reagent bottle.



---

**6.3026.150 Exchange Unit 5 mL**

Exchange Unit with integrated data chip with 5 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, anti-diffusion buret tip and standard amber glass reagent bottle.



---

**6.3026.210 Exchange Unit 10 mL**

Exchange unit with integrated data chip with 10 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, anti-diffusion buret tip and standard amber glass reagent bottle.



---

**6.3026.250 Exchange unit 50 mL**

Exchange unit with integrated data chip with 50 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, antiffusion tip and standard amber glass reagent bottle.

