

Accessories for MVA-11

Below, the accessories are grouped into Scope of delivery and Optional accessories.
Please keep this printout at hand for ordering replacement material.
These lists may be subject to change.

Scope of delivery MVA-11






Qty.	Order no.	Description
1 pcs	2.797.0030	797 VA Computrace for CVS

The 797 VA Computrace is a modern voltammetric measuring stand that is connected to a PC via a USB port. The computer software provided controls the measurement, records the measured data and evaluates it. Operation is most straightforward due to the well-laid-out structure of the program. The integrated potentiostat with galvanostat guarantees the highest sensitivity with reduced noise.

Voltammetry system for the determination of organic additives in electroplating baths with "Cyclic Voltammetric Stripping" (CVS). Complete accessories with VA Computrace software and all electrodes for a complete measurement system: Rotating platinum disk electrode (RDE), Ag/AgCl reference electrode and Pt auxiliary electrode.



Optional accessories

Order no.	Description	
2.800.0010	800 Dosino	
	Drive with write/read hardware for intelligent Dosing Units. With fixed cable (length 150 cm).	
6.1204.170	3 mm platinum electrode tip for CVS	
	Metal electrode tip made of platinum (Pt), diameter of electrode disk 3 mm, polished surface, M3 thread connection. Temperature range: 0 - 40 °C.	
6.1204.190	1 mm platinum electrode tip for CVS	
	Metal electrode tip made of platinum (Pt), diameter of electrode disk 1 mm \pm 0.02 mm, polished surface, shaft made of glass, M3 thread connection. Concentricity error: < 0.2 mm. Temperature range: 0 - 50 °C.	
6.3032.120	Dosing Unit 2 mL	
	Dosing unit with integrated data chip with 2 mL glass cylinder and light protection, mountable on reagent bottle with ISO/DIN GL45 glass thread. FEP tubing connection, anti-diffusion buret tip.	
6.3032.250	Dosing Unit 50 mL	
	Dosing unit with integrated data chip with 50 mL glass cylinder and light protection, mountable on reagent bottle with ISO/DIN GL45 thread. FEP tubing connection, anti-diffusion buret tip.	