










Accessories for 2.1008.3010

Below, the accessories are grouped into Scope of delivery and Optional accessories. Please keep this printout at hand for ordering replacement material. These lists may be subject to change.

Scope of delivery 2.1008.3010

Qty.	Order no.	Description	
1 pcs	1.1008.0010	Eco Titrator	
		<p>The compact Eco Titrator with integrated magnetic stirrer and touch-sensitive User Interface is ideal for routine analysis. It provides GLP-compliant results with minimum space requirements at all times (approx. DIN A4).</p> <p>Universally compatible with almost all potentiometric titrations, such as, for example, for</p> <ul style="list-style-type: none"> • Food products: Acid content, chloride, Vitamin C, iodine and peroxide number in fats • Water analysis: Carbonate and Ca/Mg hardness, chloride, sulfate, permanganate index • Petrochemistry: Acid/base number, sulfide & mercaptans, chloride, bromine number • Electroplating: Total acid, metal content, chloride • Surfactant analysis: Anionic, cationic and non-ionic surfactants • Photometry with the Optrode: p and m value, metals, water hardness 	
1 pcs	6.0229.010	Solvotrode easyClean (fixed cable 1.2 m)	
		<p>Combined pH electrode with flexible easyClean diaphragm and fixed cable (1.2 m) for all non-aqueous acid/base titrations. The glass membrane is optimized for poorly conducting solutions, and thanks to the easy-to-clean easyClean diaphragm, the electrode is well suited for heavily contaminated samples, such as used oil. This electrode can be used with non-aqueous reference electrolytes (lithium chloride or tetraethylammonium bromide). Storage in the respective reference electrolyte.</p>	
1 pcs	6.03002.220	20 mL cylinder unit for Eco Dosimat / Eco Titrator	
		20 mL cylinder unit for Eco Dosimat / Eco Titrator. Without dosing tubing and antidiffusion tip.	
1 pcs	6.1446.030	Ball stopper / B-14/(15)	
		For the movable holding of buret tips in titration vessels	

1 pcs	6.1446.080	Threaded stopper / M8	
1 pcs	6.1543.200	Titration tip / M6 thread Titration tip with antidiffusion valve.	
1 pcs	6.1546.040	Piston tool for Eco Dosimat/Eco Titrator Tool for removing and mounting the piston.	
1 pcs	6.1602.105	Bottle attachment / GL 45 / green For direct dosing from reagent bottles with GL 45 thread.	
1 pcs	6.1608.023	Amber glass bottle / 1000 mL / GL 45 For Exchange Units. Bottle for auxiliary solutions.	

1 pcs **6.1619.010** **Adsorber complete, for Exchange Unit**



1 pcs **6.1805.090** **FEP tubing / M6 / 31 cm**
With light and kink protection



1 pcs **6.1805.100** **FEP tubing / M6 / 40 cm**
With light and kink protection



1 pcs **6.1819.020** **Tube**
For M6 threaded holes. For 6.1602.1XX bottle attachments



1 pcs **6.1903.020** **Stirring bar / 16 mm**
Stirring Bar with magnetic core, PTFE coated, length 16 mm



1 pcs **6.1903.030** **Stirring bar / 25 mm**
Stirring bar with magnetic core, PTFE covering, length 25 mm.



1 pcs **6.2013.010** **Clamping ring**
For support rods with a diameter of 10 mm.



1 pcs **6.2016.070** **Support rod / 400 mm**



1 pcs **6.2021.020** **Electrode holder**
Electrode holder for 4 electrodes and 2 buret tips



1 pcs **6.2023.020** **Clip for SGJ 14/15**
Clip for SGJ 14/16



1 pcs **6.2164.010** **Power supply unit 100 - 240 V/24 V DC**
Power supply unit for 915 KF Ti-Touch and 916 Ti-Touch



1 pcs **6.2709.070** **Guiding sleeve**
For fixation of buret and dosing tips in titration heads and electrode holders



1 pcs **6.6081.010** **USB flash drive for Eco Titrator**
Storage medium for Eco Titrator



Optional accessories

Order no.	Description
2.142.0100	Custom Q3X thermal printer

Compact printer with USB interface for

- 900 Touch Control
- 915 KF Ti-Touch
- 916 Ti-Touch
- 917 Coulometer
- 877 / 848 Titrino plus
- 865 / 876 Dosimat plus
- 91X Meter (cable 6.2151.140)
- Eco Dosimat / Titrator
- 862 Compact Titrosampler
- 870 KF Titrino plus
- 899 Coulometer



Paper width 60 mm (40 characters). Including 6.2151.120 USB cable.
