






Accessories for 2.712.0010

Below, the accessories are grouped into Scope of delivery and Optional accessories.
Please keep this printout at hand for ordering replacement material.
These lists may be subject to change.

Scope of delivery 2.712.0010

Qty.	Order no.	Description	
1 pcs	6.2013.010	Clamping ring For support rods with a diameter of 10 mm.	
1 pcs	6.2016.050	Support rod / 300 mm	
1 pcs	6.2021.020	Electrode holder Electrode holder for 4 electrodes and 2 buret tips	

Optional accessories

Order no.	Description	
2.728.0021	728 Magnetic Swing-out Stirrer without stand, 110 V US	
	For mounting on a stand rod 10 mm dia.; without base plate (or holder) and without stand rod; incl. 6.2119.020 power adapter. U = 100...120 V, US plug.	
2.728.0024	728 Magnetic Stirrer without stand, 220 V EU	
	For mounting on a stand rod 10 mm dia.; without base plate (or holder) and without stand rod; incl. 6.2117.020 power adapter. U = 220...240 V, EU plug.	
6.0908.110	Conductivity measuring cell c = 0.8 cm⁻¹ with Pt100 (fixed cable)	
	Conductivity measuring cell with cell constant $c = 0.8 \text{ cm}^{-1}$, with integrated Pt100 temperature sensor and fixed cable (4 x B (4 mm)). This sensor is suitable for measurements of medium conductivities (1 $\mu\text{S/cm}$ to 100 mS/cm), e.g. in: <ul style="list-style-type: none"> • drinking water • surface water • waste water 	
6.1236.040	Sleeve with SGJ 14/12 mm	
	For electrodes without standard ground joint.	

6.1414.010 **Titration vessel lid with 5 openings**



6.1418.250 **Titration vessel with thermostat jacket / 50-150 mL**



6.2103.090 **Adapter F-BNC**

For connection of BNC plugs to type F sockets



6.2104.000 **Adapter cable E-F**

Connection of electrodes with type E plug (=DIN plug) to instruments with type F socket (mini-socket)



6.2125.010 **RS-232 cable 3 m, 25-pin – 9-pin**

Connecting RS-232 interface to IBM PC AT or compatible computer. Adapter 25-pin to 9-pin



6.2125.020 **RS-232 cable 3 m, 25-pin – 25-pin**

Connecting Metrohm RS-232 interface with Seiko printer DPU-41X, AND or Mettler balances (option 011, 012). For 691, 692, 713 pH Meters, Titrinos, or 737 KF Coulometer. RS-232 extension cable (1:1) with special EMC shielding.



6.2125.050 **RS-232 cable, 25-pin plug**

Connecting Metrohm RS-232 interface to Epson printer LX 300. Used with 691, 692, 713 pH Meters, Titrinos, and 737 KF Coulometer.



6.2125.060 Connection cable RS-232 to IBM PC

Connecting Metrohm RS-232 interface to PC. Used with 691, 692, 713 pH Meters, Titrinos, and 737 KF Coulometer

