









## Accessories for 2.876.0110

Below, the accessories are grouped into Scope of delivery and Optional accessories. Please keep this printout at hand for ordering replacement material. These lists may be subject to change.

### Scope of delivery 2.876.0110

| Qty.  | Order no.  | Description  |   |
|-------|------------|--|---|
| 1 pcs | 1.801.0010 | 801 Stirrer  |    |
|       |            | Magnetic stirrer without stand for supplementing the Titrino plus, Dosimat plus, Titrandos, Sample Processors, 805 Dosimats and 780/781 pH Meters. With permanently attached cable for MSB (Metrohm Serial Bus).   |   |
| 1 pcs | 1.876.0010 | 876 Dosimat plus   |   |
|       |            | <p>Universal dispensing unit for manual titrations and dosings. Including push-button cable for manual dosing control and 20 mL exchange unit. A multitude of instruments can be connected at the USB interface of the Dosimat plus, even a number of them simultaneously when a USB hub is used (keyboard, mouse, USB compact printer or USB DIN A4 printer, USB Memory Stick for methods and data backup). The optional 6.2148.030 USB/RS-232 Adapter Box enables the connection of laboratory balances and operation with a computer. With its two dosing modes, the Dosimat plus offers the following applications:</p> <p>DOS (Dosing) – Dosing at the press of a button</p> <p>This mode is particularly suitable for performing manual titrations with indicator. A result can be calculated and a result report can be printed automatically from the dosed volume.</p> <p>XDOS (Extended dosing) – Controlled dosing</p> <ul style="list-style-type: none"> <li>• Fixed volume dosing: The volume and the dosing rate are specified.</li> <li>• Time-controlled dosing: The volume and the time are specified.</li> <li>• Dosing according to dosing rate: The dosing rate and the time are specified.</li> </ul> |   |
| 1 pcs | 6.1903.020 | Stirring bar / 16 mm   |  |
|       |            | Stirring Bar with magnetic core, PTFE coated, length 16 mm   |   |

|  |            |  |   |
|--|------------|--|---|
| 1 pcs  | 6.1903.030 | <b>Stirring bar / 25 mm</b>              |    |
| Stirring bar with magnetic core, PTFE covering, length 25 mm.                                |            |  |   |
| 1 pcs  | 6.2001.060 | <b>Support stand without support rod</b> |   |
| To attach an 801, 804, 803 Stirrer to a Titrande, Titrino plus, Dosimat plus or 856 and 867. |            |  |   |
| 1 pcs  | 6.2013.010 | <b>Clamping ring</b>                     |  |
| For support rods with a diameter of 10 mm.   |            |  |   |
| 1 pcs  | 6.2016.070 | <b>Support rod / 400 mm</b>              |  |
| 1 pcs  | 6.2021.020 | <b>Electrode holder</b>                  |  |
| Electrode holder for 4 electrodes and 2 buret tips   |            |  |   |

---

**1 pcs**      **6.2107.100**      **Manual dosing controller**  
Manual dosing controller for dosing and manual titration with the Dosimat plus



---

**1 pcs**      **6.2151.100**      **Adapter USB MINI (OTG) - USB A**  
For connecting USB instruments.



---

**1 pcs**      **6.2621.070**      **5 mm hex key for IC Sample Processors**



---

**1 pcs**      **6.2621.130**      **Hexagon key 2 mm**  
2 mm.



---

**1 pcs**      **6.2739.010**      **Wrench**  
For exchange units.



---

**1 pcs**      **6.3026.220**      **Exchange Unit 20 mL**  
Exchange unit with integrated data chip with 20 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, anti-diffusion buret tip and standard amber glass reagent bottle.



## Optional accessories

| Order no. | Description |
|-----------|-------------|
|-----------|-------------|

**2.142.0100**                      **Custom Q3X thermal printer**

Compact printer with USB interface for

- 900 Touch Control
- 915 KF Ti-Touch
- 916 Ti-Touch
- 917 Coulometer
- 877 / 848 Titrino plus
- 865 / 876 Dosimat plus
- 91X Meter (cable 6.2151.140)
- Eco Dosimat / Titrator
- 862 Compact Titrosampler
- 870 KF Titrino plus
- 899 Coulometer



Paper width 60 mm (40 characters). Including 6.2151.120 USB cable.

**2.805.0010**                      **805 Dosimat**

Dosing device for the Titrando and Sample Processors with read/write hardware for intelligent Exchange Units. With permanently attached cable. Without Exchange Unit.



**6.2134.120**                      **Cable RS-232 to Mettler AX**

Connecting Metrohm RS-232 interface to Mettler AX



**6.2147.000**                      **Numerical USB keypad**

Numerical USB keypad for Titrino plus, Dosimat plus, 862 Compact Titrosampler, 869 Compact Sample Changer, 863 Compact Autosampler and 899 Coulometer. With two integrated USB connectors.



---

**6.2148.030 RS-232/USB Box**

Extends the Titrino plus by two RS-232 interfaces, e.g., for the connection of balances, PC (tiBase software), LIMS. Requires 6.2151.030 cable.



---

**6.2151.120 Cable USB MINI (OTG) - USB B, 1.8 m**

For connecting USB instruments.



---

**6.2723.310 Protective cover for Titrino plus**

Protective cover for display and keypad for all instruments of the Titrino plus family.



Suitable for: 848 Titrino plus, 862 Compact Titrosampler, 863 Compact Autosampler, 865 Dosimat plus, 869 Compact Sample Changer, 870 KF Titrino plus, 876 Dosimat plus, 877 Titrino plus, 899 Coulometer.

---

**6.3026.110 Exchange Unit 1 mL**

Exchange Unit with integrated data chip with 1 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, antidiffusion buret tip and standard amber glass reagent bottle.



---

**6.3026.150 Exchange Unit 5 mL**

Exchange Unit with integrated data chip with 5 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, anti-diffusion buret tip and standard amber glass reagent bottle.



---

**6.3026.210 Exchange Unit 10 mL**

Exchange unit with integrated data chip with 10 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, anti-diffusion buret tip and standard amber glass reagent bottle.



---

**6.3026.250 Exchange unit 50 mL**

Exchange unit with integrated data chip with 50 mL glass cylinder and light protection. PCTFE/PTFE flat stopcock, FEP tubing connection, antidiffusion tip and standard amber glass reagent bottle.

